

4-Channel 1080P DVR 3520DV300 program

1. Motherboard configuration

Master	RAM	FLASH	AD chip	hard disk
3520DV300	2G	16M	2833/2826	1

2.Support mode

Channel	Channel mode (Analog channel + digital channel)		Playback
	Serial number	Number of lines * resolution / frame rate	Number of lines * resolution / frame rate
4CH	1	4 * 1080P/15 + 0	2 * 1080P/15
	2	4 * 1080N/25 + 0	4 * 1080N/25
	3	2 * 1080P/25 + 2 * 1080P/25	2 * 1080P/25
	4	0 + 8 * 1080P/25	4 * 1080P/25
	5	0 + 4 * 3M/25	2 * 3M/25

Note: Snapshots are not supported.

3. Features

- TVI / AHD / DVR / NVR / CVI five-in-one, many kinds of mode to switch, support full HD analog, HD analog plus digit HD, full digit HD.
- Through Cloud service, easily realize net penetration, only one step to achieve remote viewing.
- Support mobile phone view. (iPhone Android)。
- Support many kinds of Web browsers. (IE/Chrome/Firefox/Safari)。
- Support VGA、TV、and HDMI output at the same time.
- Powerful network service (DHCP、PPPOE、FTP、DNS、DDNS、NTP、UPNP、Email etc.) Perfect supporting (WEB、Client 、SDK), easily achieve interconnection.
- Support twenty more kinds of languages.
- Freely Change boot logo and choose interface style.

4. Technical parameters

system	Compression format	H.264
	operating system	Embedded Linux operating system
video	enter	4
	VGA output	Yes
	BNC output	Yes
	Loop output	NO
	HDMI output	Yes
Audio	Audio Input	4
	Audio output	1
	Two-way intercom	Yes
Video	Video mode	Timing, manual, dynamic detection, external alarm
Playba ck	The number of simultaneous playback	2
	Search mode	Time point retrieval, calendar retrieval, event retrieval, channel retrieval
Backup	USB mobile hard disk, U disk	Yes
	USB DVD burner	Yes
	Backup file format	DAV、AVI
remote access	Browser	Supports multiple web browsers
	CMS	Support CMS3.0
	APP	Support for iPhone, Android
Alarm	Alarm input	4
	Alarm Output	1
storage	HDD Number	2
	E-SATA	NO
PTZ	interface	1*RS485
	protocol	PELCOP,PELCOD,LILIN,MINKING,NEON,STAR,VIDO,DSCP,VISCA,SAMSUNG,RM110,HY
	control method	Pan, Tilt, Zoom, Preset, Cruise, Trace
Netwo rk	Network port	10 / 100 Mbps Ethernet (RJ-45)
	Network protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
other	remote control	Yes
	power supply	DC12V /4A
	Work Temperature	-10° C ~60° C
	Working humidity	10% ~ 90% Humidity